

CLAIM AMENDMENTS

1. (currently amended) A base fabric for a hollow-woven air bag, comprising:
a bag portion (~~multiple fabric portion~~) formed by connecting a plurality of cloth pieces by hollow weaving;
a ~~fastened-portion~~ single layer that is interwoven by a yarn A connected to said bag portion (~~multiple fabric portion~~); and
a ~~fastened-portion~~ single layer that is interwoven by a yarn B of a weave structure different from that of said ~~fastened-portion~~ single layer that is interwoven by a yarn A, which is formed in a boundary portion between said bag portion (~~multiple fabric portion~~) and said ~~fastened-portion~~ single layer that is interwoven by a yarn A,
wherein the weave structure of the single layer that is interwoven by a yarn B has warps and/or wefts of at least one line existing in a boundary face with the bag portion interlaced in the order opposite to that of an end line of the bag portion.

2.-3. (canceled)

2 A. (currently amended) The A base fabric for a hollow-woven air bag, comprising ~~according to claim 2~~,
a bag portion formed by connecting a plurality of cloth pieces by hollow weaving;
a single layer that is interwoven by a yarn A connected to the bag portion; and
a single layer that is interwoven by a yarn B of a weave structure different from that of said single layer that is interwoven by a yarn A, which is formed in a boundary portion between said bag portion and said single layer that is interwoven by a yarn A.

wherein the weave structure of said ~~fastened-portion~~ single layer that is interwoven by a yarn B has is that warps and/or wefts of at least one line two lines existing in the a boundary face with the ~~fastened-portion~~ single layer that is interwoven by a yarn A are interlaced in the order opposite to that of the end line of the an ~~fastened-portion~~ single layer that is interwoven by a yarn A.

3 B. (currently amended) The A base fabric for a hollow-woven air bag, comprising ~~according to claim 1~~,

a bag portion formed by connecting a plurality of cloth pieces by hollow weaving;
a single layer that is interwoven by a yarn A connected to the bag portion; and

a single layer that is interwoven by a yarn B of a weave structure different from that of said single layer that is interwoven by a yarn A, which is formed in a boundary portion between said bag portion and said single layer that is interwoven by a yarn A,

wherein a yarn of an upper fabric and a yarn of a lower fabric which form said bag portion (~~double bag portion~~) have a weave structure in which said yarns of the upper and lower fabrics are crossed with each other at least once in such a manner that said yarn of the upper fabric passes under said yarn of the lower fabric and said yarn of the lower fabric passes ~~on~~ over said yarn of the upper fabric.

4 ~~/~~. (currently amended) A base fabric for a hollow-woven air bag, comprising a bag portion (~~multiple fabric portion~~) formed by connecting a plurality of cloth pieces each made by warps and wefts by hollow weaving, wherein a rate of variation in a crimp ratio of all of said warps is 40% or less.

5 ~~/~~. (original) The base fabric for a hollow-woven air bag according to claim 6, wherein a rate of variation in thickness in the width direction of said base fabric for an air bag is 3% or less.

6 ~~/~~. (original) The base fabric for a hollow-woven air bag according to claim 6, wherein a rate of variation in a crimp ratio of all of said warps is 30% or less.

7 ~~/~~. (original) The base fabric for a hollow-woven air bag according to claim 6, wherein a rate of variation in a crimp ratio of all of said warps is 15% or less.

8 ~~/~~. (original) The base fabric for a hollow-woven air bag according to claim 6, wherein a rate of variation in a crimp ratio of all of said warps is 10% or less.

9 ~~/~~. (currently amended) An air bag comprising a base fabric for an air bag for forming a bag portion, and an inflator attaching port provided for said bag portion, wherein said base fabric for an air bag comprises:
said bag portion (~~multiple fabric portion~~) formed by connecting a plurality of cloth pieces by hollow weaving;
a ~~fastened portion~~ single layer that is interwoven by a yarn A connected to said bag portion (~~multiple fabric portion~~); and

a ~~fastened portion~~ single layer that is interwoven by a yarn B of a weave structure different from that of said fastened portion single layer that is interwoven by a yarn A, which is formed in a boundary portion between said bag portion (multiple fabric portion) and said fastened portion single layer that is interwoven by a yarn A.

wherein the weave structure of the single layer that is interwoven by a yarn B has warps and/or wefts of at least one line existing in a boundary face with the bag portion interlaced in the order opposite to that of an end line of the bag portion.

12.-13. (canceled)

- 10 ~~14.~~ (currently amended) The An air bag comprising according to claim 12,
(a) a base fabric for an air bag for forming a bag portion, and
(b) an inflator attaching port provided for the bag portion,
wherein the base fabric for an air bag comprises:
the bag portion formed by connecting a plurality of cloth pieces by hollow weaving;
a single layer that is interwoven by a yarn A connected to the bag portion; and
a single layer that is interwoven by a yarn B of a weave structure different from that of said single layer that is interwoven by a yarn A, which is formed in a boundary portion between said bag portion and said single layer that is interwoven by a yarn A,

wherein the weave structure of said fastened portion single layer that is interwoven by a yarn B has is that warps and/or wefts of at least one line two lines existing in the a boundary face with the fastened portion single layer that is interwoven by a yarn A are interlaced in the order opposite to that of the an end line of the fastened portion single layer that is interwoven by a yarn A.

- 11 ~~15.~~ (currently amended) An air bag comprising The base fabric for a hollow-woven air bag according to claim 11,
(a) a base fabric for an air bag for forming a bag portion, and
(b) an inflator attaching port provided for the bag portion,
wherein the base fabric for an air bag comprises:
the bag portion formed by connecting a plurality of cloth pieces by hollow weaving;
a single layer that is interwoven by a yarn A connected to the bag portion; and
a single layer that is interwoven by a yarn B of a weave structure different from that of said single layer that is interwoven by a yarn A, which is formed in a boundary portion between said bag portion and said single layer that is interwoven by a yarn A,

wherein a yarn of an upper fabric and a yarn of a lower fabric which form said bag portion (~~double bag portion~~) have a weave structure in which said yarns of the upper and lower fabrics are crossed with each other at least once in such a manner that said yarn of the upper fabric passes under said yarn of the lower fabric and said yarn of the lower fabric passes ~~on~~ over said yarn of the upper fabric.

- 12 ~~16~~. (currently amended) An air bag comprising
(a) a base fabric for an air bag for forming a bag portion and
(b) an inflator attaching portion provided for said bag portion,
wherein said base fabric for an air bag comprises:
said bag portion (~~multiple fabric portion~~) formed by connecting a plurality of cloth pieces each made by warps and wefts by hollow weaving,
wherein a rate of variation in a crimp ratio of all of said warps is 40% or less.

13 ~~17~~. (original) The air bag according to claim ¹²~~16~~, wherein a rate of variation in thickness in the width direction of said base fabric for an air bag is 3% or less.

14 ~~18~~. (currently amended) ¹²The air bag according to claim ~~16~~. ~~The base fabric for a hollow woven air bag according to claim 16,~~ wherein a rate of variation in a crimp ratio of all of said warps is 30% or less.

15 ~~19~~. (currently amended) ¹²The air bag according to claim ~~16~~. ~~The base fabric for a hollow woven air bag according to claim 16,~~ wherein a rate of variation in a crimp ratio of all of said warps is 15% or less.

16 ~~20~~. (currently amended) ¹²The air bag according to claim ~~16~~. ~~The base fabric for a hollow woven air bag according to claim 16,~~ wherein a rate of variation in a crimp ratio of all of said warps is 10% or less.

- 17 ~~21~~. (currently amended) A side-impact protection air bag comprising:
(a) a base fabric for an air bag for forming a bag portion; and
(b) an inflator attaching port provided for said bag portion,
wherein said base fabric for an air bag comprises

said bag portion (~~multiple fabric portion~~) formed by connecting a plurality of cloth pieces made by warps and wefts by hollow weave, and a rate of variation in crimp ratio of all of said warps is 40% or less.

~~18~~ ¹⁷22. (original) The side-impact protection air bag according to claim ~~21~~, wherein a rate of variation in thickness in the width direction of the base fabric for an air bag is 3% or less.

~~19~~ ²³23. (new) The base fabric for a hollow-woven air bag according to claim 1, wherein said single layer that is interwoven by a yarn B has 1 to 20 warps and/or wefts.

~~20~~ ²⁴24. (new) The base fabric for a hollow-woven air bag according to claim ~~4~~ ², wherein said single layer that is interwoven by a yarn B has 1 to 20 warps and/or wefts.

~~21~~ ⁹25. (new) The air bag for a hollow-woven air bag according to claim ~~11~~ ⁹, wherein said single layer that is interwoven by a yarn B has 1 to 20 warps and/or wefts.

~~22~~ ¹⁰26. (new) The air bag for a hollow-woven air bag according to claim ~~14~~ ¹⁰, wherein said single layer that is interwoven by a yarn B has 1 to 20 warps and/or wefts.